redmineorg-copy202205 - Vote #64239

Pb with CVS Server when CVSROOT does not contain user name

2022/05/09 13:43 - Admin Redmine

ステータス:	Closed	開始日:	2008/12/06
優先度:	通常	期日:	
担当者:		進捗率:	0%
カテゴリ:	SCM_3	予定工数:	0.00時間
対象パージョン:	0.8_2	作業時間:	0.00時間
Redmineorg_URL:	https://www.redmine.org/issues/2286	status_id:	5
category_id:	3	tracker_id:	1
version_id:	2	plus1:	0
issue_org_id:	2286	affected_version:	
author_id:	3005	closed_on:	
assigned_to_id:	0	affected_version_id:	5
comments:	2		

説明

Depending on the CVS configuration, it is not mandatory to include a username in the CVSROOT.

For example, a valid CVSROOT is :ext:cvsservername:/cvsdatabase/projects1

With this CVSROOT format, redmine does not import correctly the information from CVS but does not report any error.

When configuring the CVSROOT with a username, :ext:username@cvsservername:/cvsdatabase/projects1, everything goes well.

The problem comes from the file name lib/redmine/scm/adapters/cvs_adapter.rb. In the regulare expression line 137 root_url.gsub(/::@[i*:d/, ''), the @ should be optional.

journals

I forget one char in the previous description.

The problem comes from the file name lib/redmine/scm/adapters/cvs_adapter.rb.

In the regular expression line 137 root_url.gsub(/:[1+:/d/, ''), the @ should be optional.

Fixed in r2096. Thanks for pointing this out.

履歴

#1 - 2022/05/10 17:27 - Admin Redmine

- カテゴリ を SCM_3 にセット
- *対象バージョン を* 0.8_2 *にセット*

2024/04/25 1/1