

implement an upgrade script

2022/05/09 18:22 - Admin Redmine

ステータス:	New	開始日:	2022/05/09
優先度:	通常	期日:	
担当者:		進捗率:	0%
カテゴリ:		予定工数:	0.00時間
対象バージョン:		作業時間:	0.00時間
Redmineorg_URL:	https://www.redmine.org/issues/26847	status_id:	1
category_id:	0	tracker_id:	2
version_id:	0	plus1:	0
issue_org_id:	26847	affected_version:	
author_id:	115380	closed_on:	
assigned_to_id:	0	affected_version_id:	
comments:	0		
説明 User can do mistake when they upgrade an existing instance, for example overwrite files in public from an older release. Some ideas <pre>#!/bin/bash redmine_version='3.4.2' archive_path='...' www_path='...' pushd \${www_path} tar xzf \${archive_path}/redmine-\${redmine_version}.tar.gz chown -R apache.apache redmine-\${redmine_version} pushd redmine-\${redmine_version} cp \${www_path}/redmine/config/database.yml config/ cp \${www_path}/redmine/config/configuration.yml config/ cp -r \${www_path}/redmine/plugins/* plugins/ # cp -r \${www_path}/redmine/public/... public/ cp -r \${www_path}/redmine/files/* files/ # patch -p0 < \${www_path}/redmine-patch.diff bundle install --without development test bundle exec rake generate_secret_token bundle exec rake db:migrate RAILS_ENV=production bundle exec rake tmp:cache:clear tmp:sessions:clear RAILS_ENV=production popd rm redmine ln -sf redmine-\${redmine_version} redmine apachectl restart</pre>			